



## Compact, Highly Efficient Multifunction Printers.

These new multifunction devices offer all the benefits of a professional document management solution for workgroups and small offices. Featuring advanced functionality, easy to operate touchscreen, and the integrated solution platform HyPAS™. Cost-efficient and eco-friendly offices will appreciate Kyocera's unique ECOSYS® technology which increases operating life, reduces environmental impact, cuts printing costs and ensures reliability.

- ▶ HyPAS solution platform enables powerful customisation
- ▶ Up to 30 pages per minute (A4) in colour or monochrome
- ▶ Time to first copy: 9.2 seconds or less
- ▶ Professional print, copy, scan and fax functionality†
- ▶ Paper capacity up to 1,600 sheets and a range of paper-handling options
- ▶ Easy to install and operate
- ▶ Easy to use wizard-style navigation
- ▶ Low noise emissions match desktop printers
- ▶ Compact, 360° all-round stylish design to match any office
- ▶ ECOSYS Long-life components provide unprecedented efficiency and reliability
- ▶ Exceptionally low printing costs in its class





## The FS-6525MFP / FS-6530MFP includes:

### PRESCRIBE

With the Kyocera page design and control language PRESCRIBE, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

### The KYOCERA NetViewer

The KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital Kyocera multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

### Status Monitor and Command Centre

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

### USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

### HyPAS

Hybrid Platform for Advanced Solutions. Kyocera's powerful software development platform enables users to customise the functionality and operations of the MFP to their individual requirements.

## ECOSYS® Our Unique Printing Technology

ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly, and the drum units every 300,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

### General

**Technology:** KYOCERA ECOSYS, Mono Laser

HyPAS Solution Platform

**Engine speed:** FS-6525MFP - Up to 25 pages A4 per minute  
FS-6530MFP - Up to 30 pages A4 per minute

**Resolution:** 600 x 600 dpi (print, copy and scan)

**Control panel display:** 4.3 inch full-colour touch panel display

**PM cycle:** 300,000 pages

**Warm-up time:** Approx. 20 seconds or less

**Time to first print:** Approx. 8 seconds or less

**Time to first copy:** Approx. 9.2 seconds or less

**CPU:** PowerPC 464 / 800 MHz

**Memory:** Standard 1,024 MB, max. 2,048 MB

**Integrated accounting:** 100 department codes

**Dimensions (W x D x H):** 590 x 590 x 694 mm

**Weight:** Approx. 52.2 kg including toner container

**Power source:** AC 220 ~ 240 V, 50/60 Hz

**Safety standards:** AS / NZ53260 / C-TICK

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

### Paper Handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm (80gsm). Please use paper recommended by Kyocera under normal environmental conditions.

**Input capacity:** 100-sheet multi-purpose tray, 45-256 gsm, 200 mm (Postcard); 52-163 gsm (larger than A4 / Letter size), A3, A4, A5, A6, B5, Letter, Legal, Folio, envelopes, Custom (98 x 148 to 297 x 432 mm) 500-sheet universal paper cassette, 60-163 gsm, A3, A4, A5, A6, B5, Letter, Legal, Folio, max. input capacity with options: 1,600 sheets

**Duplex unit:** Duplex as standard supports 60-163 gsm A3-A5R

**Reversing document processor:** 50-sheet, Simplex scan 45-160 gsm, Duplex scan 50-120 gsm, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm)

**Output capacity:** Max. 300 sheets; 250 sheets face-down (main tray), plus 50 sheets (job separator tray)

### Print functions

**Controller language:** PRESCRIBE

**Emulations:** PCL 6 (5e/XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

**Interface:** USB 2.0 (High-Speed), USB Host 2.0, Fast Ethernet 10/100/1,000Base-TX, Slot for optional print server, Slot for optional Memory Card

**Operating systems:** All current Windows operating systems, MAC OS X Version 10.2 or higher, Unix, Linux as well as other operating systems on request

**Fonts/bar codes:** 93 outline fonts (PCL 6, KPDL3) + 8 (Windows Vista), OCR: OCR-A, OCR-A kana, OCR-B, OCR-B kana, OCRkana bitmap fonts, 45 types of one-dimensional bar codes, 1 type of two-dimensional bar code (PDF 417) - via PRESCRIBE

**Features:** encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3

### Copy functions

**Max. original size:** A3/Ledger

**Continuous copying:** 1-999 Zoom range: 25-400% in 1% steps

**Preset magnification ratios:** 5 Reductions / 5 Enlargements

**Features:** Scan-once-copy-many, sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through

**Exposure mode:** Auto, manual: 7 steps

**Image adjustments:** Text, Photo, Text + Photo, Graphic/Map, Copy/Printout

### Scan functions

**Functionality:** Scan-to-Email, Scan-to-FTP, Scan-to-PC, Scan to USB Host, TWAIN, WSD scan

**Interface:** Fast Ethernet 10/100/1000Base-TX, USB Host 2.0

**Scan speed:** 40 ipm (300 dpi, A4, mono), 20 ipm (300 dpi, A4 colour)

**Scan resolution:** 600, 400, 300, 200 dpi (256 greyscales per colour)

**Max. scan size:** A3, Ledger

**File types:** TIFF, PDF, JPEG, XPS

**Features:** Integrated address book, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once

### Fax functions

**Compatibility:** ITU-T Super G3

**Modem speed:** Max. 33.6 kbps

**Transmission speed:** Less than 3 sec

**Scanning speed:** 2.0 seconds (Quick Scanning, Bitmap)

**Address book:** 200 entries

**Interface:** Fast Ethernet 10/100/1000Base-TX, Telephone interface

**Scanning density:**

**Normal:** 8 dot/mm x 3.85 line/mm

**Fine:** 8 dot/mm x 7.7 line/mm

**Superfine:** 8 dot/mm x 15.4 line/mm

**Ultrafine:** 16 dot/mm x 15.4 line/mm

**Halftone:** 8 dot/mm x 7.7 line/mm

**Maximum original size:** A3, Ledger

**Compression method:** JBIG, MMR, MR, MH

**Memory reception:** 700 sheets or more

**Features:** Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

### Options

#### Paper handling

**PF-470 Paper feeder:** Max. 500 sheets; 60-163 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

**PF-471 Paper feeder:** Max. 1,000 sheets; 60-163 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

**DF-470 Document finisher:** Max. 500 sheets 52-256 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

**AK-470 Bridge Unit:** To be used with DF-470

### Memory upgrade

DIMM-1GB: 1024 MB

### Others

**USB Flash Memory:** Supports direct printing and scanning of PDF, XPS, TIFF, JPEG files via USB Host interface

### Optional Interfaces

**Fax System:** Type U

**Additional network card:** IB-50

### Consumables

**TK-479 Toner Kit:** Microfine toner black for 15,000 pages A4 in accordance with ISO/IEC 19752

Capacity of starter toner is 3,000 pages in accordance with ISO/IEC 19752

### Warranty

3-year warranty as standard to a maximum 180,000 pages for FS-6530MFP and 150,000 pages for FS-6525MFP - whichever occurs sooner, provided the printer is used and cleaned in accordance with the service instructions.



HyPAS™



The images displayed in this brochure are for illustrative purposes only, and may include optional extras.

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. † Fax Functionality optional.

**KYOCERA Document Solutions Australia**  
Ph: 13 KYOCERA (596 2372)  
www.KyoceraDocumentSolutions.com.au

**KYOCERA Document Solutions New Zealand**  
Ph: 0508 KYOCERA (596 2372)  
www.KyoceraDocumentSolutions.co.nz

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

**KYOCERA**  
Document Solutions